

Armored Mercedes-Benz 5550

ALPINE ARMORING INC.

alpineco.com



Table of Contents	Page 2
Vehicle Specifications	Page 3
Opaque Armor Details	Page 4
Transparent Armor Details	Page 5
Additional Features	Page 6
Completed Vehicle Photos	Page 7-8
Ballistic Reference Chart	Page 9
Vehicle Warranty	Page 10

GENERAL SPECIFICATIONS

VIN: WDDUG8CB6EA053947

MAKE: Mercedes Benz

MODEL: S550

YEAR: 2014

4.6L V8 Biturbo with Direct Injection **ENGINE:**

POWER: 449 hp

7-Speed Automatic **TRANSMISSION:**

COLOR: Black

INTERIOR: Black Leather

SEATING: 2 + 3

APPROX. WEIGHT: 6,000 lbs. (2,700 kg)

OTHER SPECIFICATIONS

HEIGHT:

58 in.

(147 cm)

WIDTH:

84 in.

(212 cm)

LENGTH:


205 in.

(520 cm)

WHEELBASE:

125 in.

(316 cm)





Firewall

Ballistic steel lines the firewall and provides protection up front.

4-1

Roof

Roof is lined with ballistic steel at angle.



4-5



Floor

Floor is lined with ballistic steel to protect against mines and grenade blasts.

4-2

Doors

All doors are lined with ballistic steel.

4-6





Exhaust Protection

The exhaust is protected by a steel mesh to prevent sabotage.

4-3

Heavy-Duty Hinges

Custom hinges that support the weight of the armored doors.

4-7





Overlaps


All doors and windows feature ballistic steel overlaps to keep shrapnel from angle shots from entering the cabin.

4-4

Wheel Wells

Front and rear wheel wells are lined with ballistic steel.

4-8







Glass Thickness

Minimum 39 mm thick glass/polycarbonate composite transparent armor.

5-1



Anti-Spall Layer

Inner-most anti-spall layer prevents glass and bullet fragments from penetrating into passenger cabin area.


5-2



Multi-Hit Protection

All windows are capable of sustaining multiple hits while providing protection to passengers.

5-3



Anchored Windows

All windows are anchored for additional protection from explosions.

5-4







P.A./Multi-Siren System

Located on the center console. The multi-siren features standard siren tones, volume adjustment, and a public address system.

6-1

Emergency Lighting

Red/blue LED lights are mounted in the front grill and visor area.





Power Windows

The front two windows are powered and lower approximately 5-6 inches for documents pass-thru.

6-2

Battery Protection

The battery is encased in a ballistic steel box.





ECM Protection

Electronic control module is encased in a ballistic steel box.

6-3

Fuel Tank Protection

The fuel tank is encased in a ballistic steel box to protect against mines and grenades.













































ALPINE ARMORING INC.

ALPINE ARMORING'S BALLISTIC CHART

WEAPONS		SPECS			LEVELS				BULLETS			protects you better" NUMBER OF SHOTS
WEST ONS	TYPE	CALIBER (mm)	CLASS	STANAG	UL	ALPINE	NIJ	CEN	MASS (9)	MATERIAL	VELOCITY	Humber of Shots
	.38 Special	9 x 19	Handgun	-	1	A1	I.II.IIA	-	8.00	(CC)	358 M/S	5
	.357 Magnam	9 x 33	Handgun		2	A2	LHA	B1 & 83	10.20	JSP	430 M/S	, —
	44 Magnum	11 x 33	Handgun	*	3	АЗ	IIIA	B4	15.60	LWC	440 M/S	j —
137	MP5	9 x 19	SMG	-	6	A4	IIIA	82	8.00	lco	427 M/S	5 -
	Shatgun	12 Gauge	Shotgun		3 & 4	Aŝ	HIA	SG2	28.30	SLUG	503 M/S	
8	Tokarev	7.62 x 25	Handgun	2	7-	A5	IIIA	-	5.50	LCSJ	488 M/S	
The same of	Kalashnikov (AK-47)	7.62 x 39	Assault Rifle	4	-	A6	111	85	9.70	SCO	732 M/S	
-	Kolashnikov (AK-47 Military)	7.62 x 39 API BZ	Assault Rifle	n	-	A7	-	85*	11.70	scc)	774 M/s	
	M16/AR-15	5.56 x 45 NATO 55109 5.56 x 45 NATO Ball	Assault Rifle	1	7	A8	IV	85	4.00	7(C) 2(C)	900 M/s 833 M/s	
	Winchester .308	7.62 x 51	Rifle	1	7	A9	III	86	10.90	ltti	810 M/s	5
	Reminighon 700 SPS	762 x 63 AP (.30-06)	High-Power Rifle	111	5 & 8	A10	IV	B7-	10,80 8,40	AΡ	869 M/s 930 M/s	5
	Drodanov	7.67 x 54R B32 API	Sniper Rifle	111	4	A11	IV+	87+	10.04	sca	854 M/s	
	50 Cal	12.7 x 99	High-Power Rifle	IV	10	A12	-	-	45.00	CJ	2/W 806	
7												_



UL Underwriters Laboratory, 752

NIJ National Institute of Justice, 0108.01

CEN European Standard

STANAG ... NATO's Standard (STANAG 4569)

ALPINE Alpine Armoring's Certified Standard

LCCJ Lead Core Copper Jacket

JSP Jacketed Soft Point LWC Lead Wad Cutter

LCSJ Lead Core Steel Jacket SCCJ Steel Core Copper Jacket

AP Armor Piercing

SG..... Shotgun

Shots (5) 11.4 cm Square Pattern (Corners & Center)

Shots (3) ..., 11,4 cm Triangular Pattern

Velocity Minimum Measured Velocity

NU Rating .. Levels I, II, IIA, & IIIA (based on 1 of 2 required calibers of ballistic threat)





